



Hans Johansson <byggis.se@gmail.com>

5" LCD-TFT Coaxial HD CCTV Tester With VGA/HDMI input!

1 meddelande

Unique Vision <simon@uniquecctv.cn>

8 maj 2017 05:32

Till: "byggis.se@gmail.com" <byggis.se@gmail.com>

If you're unable to see the message below, [click here](#) to view,

Make sure you can receive the email from us, please add us to your [white list](#),

if you don't wish to receive any more emails, you can [unsubscribe](#) here.

5" LCD-TFT Coaxial HD CCTV Tester With VGA/HDMI input!

Model: Stest-IV8A Sample Price: US\$82/pcs Support AHD/CVBS Video Test

Model: Stest-IV8S Sample Price: US\$96/pcs Support AHD/CVI/TVI/CVBS Video Test

HD CCTV Tester IV8



- 5.0 inch HVGA TFT-LCD, 800X480 resolution
- HD-CVI, HD-TVI, HD-AHD camera test, video display, coaxial
- PAL/NTSC AUTO
- VGA INPUT
- HDMI 1.0 INPUT
- PTZ control, call coaxial camera menu to set parameter
- Output 12V/1A power for camera
- Working time lasts 11 hours

Screen



HD coaxial tester with 5.0 inch LCD-TFT, 800 (RGB) x480 resolution, allows the user to view the image from sufficient angle. Support PAL/NTSC, LCD screen brightness/ contrast/ color saturation adjustable. Suitable for outdoor installation and maintenance work

Optional models

	CVBS	AHD	TVI	CVI
IV8A	•	•		
IV8T	•		•	
IV8M	•	•	•	
IV8S	•	•	•	•

Function

Model	HD coaxial tester
Video Test	
Signal mode	NTSC/PAL (Auto adapt)
Display	5.0 inch VGA TFT-LCD, 800 (RGB) x 480 resolution
LCD adjustment	Brightness, Contrast, Saturation adjustable
Video IN/OUT	1 channel BNC Input & 1 channel BNC Output
VGA/HDMI Test	

Coaxial HD Video testing

video display, PTZ control
Resolution comparison table:

	720P	1080P
CVI	25/30/50/60fps	20/30fps
TVI	25/30/50/60fps	25/30fps
AHD	25/30fps	25/30fps

Analog camera testing

- Video display, PAL/NTSC AUTO
- PTZ control, Compatible with protocols PELCO-D/P

Others

- UTP cable test, Color bar generator, Audio test, LED lamp

Front Panel



VGA/HDMI Input	Support VGA/HDMI 1.0 video input, once connect VGA/HDMI video, please switch selector to select HDMI or VGA mode. The maximum resolution is 1920X1080
PTZ Controller	
	Support RS485
PTZ Protocol	Compatible with protocols PELCO-D/P
Baud Rate	600,1200, 2400, 4800, 9600, 14400bps
Video Signal Generation	
Color bar generator	Support both PAL / NTSC format's standard color bar output (Red, Green, Blue, White, Black, Grey) and testing image output
UTP Cable Tester	
UTP cable test	Display UTP cable connection status , cable type and the sequence of wires as well as read the number of the test box.
DC12V 1A Power Output	
DC12V power output	Output DC12V1A power for camera
Audio Input Test	
Audio input test	1 channel audio signal input
TVI Test (Optional) *	
TVI video signal test	1 channel TVI input (BNC interface) , support 720p 25 / 30 / 50 / 60fps, 1080p 25 / 30fps
AHD Test (Optional) *	
AHD video signal test	1 channel AHD input (BNC interface) , support AHD 2.0 version, 720p 25 / 30fps, 1080p 25 / 30fps
Digital Multimeter (Optional) *	
AC/DC Voltage	0-660V auto/manual range, the min resolution is 0.1mV
AC/DC current	660.0uA , 6.600mA, 66.00mA , 660.0mA, 10.00A
POWER	
Power Adapter	DC 5V (1.5A)
Battery	Built-in 18650 2600mA battery X 2
Rechargeable	After charging 3-4 hour, working time lasts 11 hours
Low Consumption	Energy saving , battery capacity indicator
Parameter	
Operation setting	OSD menu, select your desired language: English, Chinese, etc
General	
Working Temperature	-10°C ~ +50°C
Working Humidity	30% ~ 90%
Dimension/ Weight	194mm x 112mm x 48mm / 540g

Thanks and Regards Simon Woo

Skype: cctvsimon, Whatsapp/Wechat: +86-13590128323

Website: www.unique-cctv.com

Address: 4th Floor, Block A, Zhongcheng Industrial Zone, East Industrial Road, Longhua Town, Shenzhen, China