

MARMO DESIGN CATALOGUE

SINAI PEARL (TRIESTA):

WINDOW SILLS BUSHHAMMERED



POLISHED



MARMO DESIGN CATALOGUE

HONED + TUMBLED



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 19 800 psi
Flexural Strength (ASTM C 880): 1 900 psi
Abrasion Resistance (ASTM C 241/ C 1353): 38.8 Ha
Density (ASTM C 97): 2.628
Water Absorption (ASTM C 97): 0.89 %
Modulus of Rupture (ASTM C 99): 1900 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face and flamed.

For more photos: <http://www.marmodesign-trade.com/#!/sinai-pearl-egyptian-marble/c5ew>

MARMO DESIGN CATALOGUE

GALALA EXTRA



GALALA CREAM



MARMO DESIGN CATALOGUE

GALALA BEIGE



Standard Specifications & Technical Data:-

Water Absorption (ASTM C 97): 0.17 %

Modulus of Rupture (ASTM C 99): 1 800 psi

Compressive Strength (ASTM C 170): 17 600 psi

Abrasion Resistance (ASTM C 24): 31.6 Ha

Flexural Strength (ASTM C 880): 1 250 psi

Density (ASTM C 97): 2 675

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!galala-marble/c17b4>

MARMO DESIGN CATALOGUE

MELLY GRAY



DARK GRAY



MARMO DESIGN CATALOGUE

DARK GRAY SPLIT FACE



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 20 200 psi
Flexural Strength (ASTM C 880): 2 300 psi
Abrasion Resistance (ASTM C 241/ C 1353): 33.9 Ha
Density (ASTM C 97): 2 662
Water Absorption (ASTM C 97): 0.05 %
Modulus of Rupture (ASTM C 99): 2 000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face and flamed.

For more photos: <http://www.marmodesign-trade.com/#/melly-grey/c22lm>

MARMO DESIGN CATALOGUE

SUNNY LIGHT



SUNNY MEDIUM



MARMO DESIGN CATALOGUE

SUNNY DARK



Standard Specifications & Technical Data:-

Water Absorption (ASTM C 97): 0.29 %

Modulus of Rupture (ASTM C 99): 2 000 psi

Compressive Strength (ASTM C 170): 13 300 psi

Abrasion Resistance (ASTM C 24): 26.4 Ha

Flexural Strength (ASTM C 880): 1 600 psi

Density (ASTM C 97): 2 618

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!/sunny/c1hdd>

MARMO DESIGN CATALOGUE

GOLDEN CREAM



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 10 300 psi
Flexural Strength (ASTM C 880): 1 200 psi
Abrasion Resistance (ASTM C 241/ C 1353): 40.1 Ha
Density (ASTM C 97): 2 561
Water Absorption (ASTM C 97): 1.42 %
Modulus of Rupture (ASTM C 99): 1 700 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!/golden-cream-egyptian-marble/c11dw>

MARMO DESIGN CATALOGUE

NEW SILVIA



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 13 300 psi
Flexural Strength (ASTM C 880): 1 600 psi
Abrasion Resistance (ASTM C 241/ C 1353): 26.4 Ha
Density (ASTM C 97): 2 618
Water Absorption (ASTM C 97): 0.29 %
Modulus of Rupture (ASTM C 99): 2 000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more Photos: <http://www.marmodesign-trade.com/#!/silvia-menia-egyptian-marble/c1k6o>

MARMO DESIGN CATALOGUE

KHATMYA (FOSSIL STONE)



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 15 600 psi
Flexural Strength (ASTM C 880): 1 400 psi
Abrasion Resistance (ASTM C 241/ C 1353): 26.5 Ha
Density (ASTM C 97): 2.567
Water Absorption (ASTM C 97): 1.31 %
Modulus of Rupture (ASTM C 99): 1600 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face and flamed.

For more photos: <http://www.marmodesign-trade.com/#!/khatmia-egyptian-marble/c1s16>

MARMO DESIGN CATALOGUE

ZAFARANA CREAM



ZAFARANA SILVIA CREAM



MARMO DESIGN CATALOGUE

ZAFARANA SILVIA ROSE



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 20 200 psi
Flexural Strength (ASTM C 880): 1 600 psi
Abrasion Resistance (ASTM C 241/ C 1353): 33.9 Ha
Density (ASTM C 97): 2.662
Water Absorption (ASTM C 97): 0.26 %
Modulus of Rupture (ASTM C 99): 2000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!/zafarana-flower-egyptian-marbl/cbxx>

MARMO DESIGN CATALOGUE

KATREEN



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 20 200 psi
Flexural Strength (ASTM C 880): 2 300 psi
Abrasion Resistance (ASTM C 241/ C 1353): 33.9 Ha
Density (ASTM C 97): 2 662
Water Absorption (ASTM C 97): 0.05 %
Modulus of Rupture (ASTM C 99): 2 000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face and flamed.

For more photos: <http://www.marmodesign-trade.com/#!/katrena-egyptian-marble/c1jhu>

MARMO DESIGN CATALOGUE

DESERT



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 15 600 psi
Flexural Strength (ASTM C 880): 1 400 psi
Abrasion Resistance (ASTM C 241/ C 1353): 26.5 Ha
Density (ASTM C 97): 2.567
Water Absorption (ASTM C 97): 1.31 %
Modulus of Rupture (ASTM C 99): 1600 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face and flamed.

For more photos: <http://www.marmodesign-trade.com/#!/desert-egyptian-marble/c1ics>

MARMO DESIGN CATALOGUE

SAMAHA LIGHT



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 20 200 psi
Flexural Strength (ASTM C 880): 1 600 psi
Abrasion Resistance (ASTM C 241/ C 1353): 33.9 Ha
Density (ASTM C 97): 2 .662
Water Absorption (ASTM C 97): 0.29 %
Modulus of Rupture (ASTM C 99): 2000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!/samaha-marble/c46x>

MARMO DESIGN CATALOGUE

NEW SUNNY



Standard Specifications & Technical Data:-

Compressive Strength (ASTM C 170): 13 300 psi
Flexural Strength (ASTM C 880): 1 600 psi
Abrasion Resistance (ASTM C 241/ C 1353): 26.4 Ha
Density (ASTM C 97): 2 618
Water Absorption (ASTM C 97): 0.29 %
Modulus of Rupture (ASTM C 99): 2 000 psi

- Country of origin: Egypt
- Material availability: Blocks, slabs, tiles
- Dimensions of the slabs: 265-300cm x 160-195cm
- Thickness of the slabs (Availability): 15-20-30-40-50mm (up to 200mm by order)
- Dimensions of the tiles (Availability): Any dimensions
- Thickness of the tiles: 10-12-15-20-30-40mm (up to 200mm by order)

Surface finishes: Polished, unpolished, honed, brushed, acid, sandblasted, bush hammered tumbled, striped, split face.

For more photos: <http://www.marmodesign-trade.com/#!/sunny-menia-egyptian-marble/cijf>